

On: 09 January 2013, At: 00:36

Publisher: Taylor & Francis

Informa Ltd Registered in England and Wales Registered Number: 1072954 Registered office: Mortimer House, 37-41 Mortimer Street, London W1T 3JH, UK



Phase Transitions: A Multinational Journal

Publication details, including instructions for authors and subscription information:

<http://www.tandfonline.com/loi/gpht20>

Guest editors' note

E.K.H. Salje^a & J. Hlinka^b

^a Department of Earth Sciences, University of Cambridge, Cambridge, UK

^b Institute of Physics, Czech Academy of Sciences, Prague, Czech Republic

Version of record first published: 23 Oct 2012.

To cite this article: E.K.H. Salje & J. Hlinka (2013): Guest editors' note, Phase Transitions: A Multinational Journal, 86:1, 1-1

To link to this article: <http://dx.doi.org/10.1080/01411594.2012.734476>

PLEASE SCROLL DOWN FOR ARTICLE

Full terms and conditions of use: <http://www.tandfonline.com/page/terms-and-conditions>

This article may be used for research, teaching, and private study purposes. Any substantial or systematic reproduction, redistribution, reselling, loan, sub-licensing, systematic supply, or distribution in any form to anyone is expressly forbidden.

The publisher does not give any warranty express or implied or make any representation that the contents will be complete or accurate or up to date. The accuracy of any instructions, formulae, and drug doses should be independently verified with primary sources. The publisher shall not be liable for any loss, actions, claims, proceedings, demand, or costs or damages whatsoever or howsoever caused arising directly or indirectly in connection with or arising out of the use of this material.

Guest editors' note

Domain boundaries can assume functionalities which do not exist in the bulk. For example, the use of active domain boundaries is well advanced for magnetic domain walls and applied in the IBM race track technology by Stuart Parkin. Similar device applications are possible in ferroelectric materials, but have only partially been explored. The matrix in this case is often a ferroelastic crystal so that the position and shape of the domain wall is defined by the twinning of the underlying bulk material. Another application with high potential for the development of disruptive technologies is the discovery of highly conducting (or even superconducting) twin walls in insulating matrices. In the area of fundamental science, it is mainly the discovery of chiralities of twin walls and the ability of twin walls to trap defects which has stimulated large research efforts. It is the purpose of this Special Issue to present a series of papers dedicated to *Domain Boundary Engineering* which allow the reader to gauge current advances and stimulate future research.

Guest Editors

E.K.H. Salje

*Department of Earth Sciences, University of Cambridge
Cambridge, UK*

J. Hlinka

Institute of Physics, Czech Academy of Sciences

Prague, Czech Republic

Email: hlinka@fzu.cz

September 2012